Construct a Stockpile with a

Crawler Tractor

Action:

Construct a stockpile with a crawler tractor.

Conditio

ns:

Given a D7G Crawler tractor, an FM 5-434, a TM 5-2410-237-10, a LO 5-2410-237-12, at a designated training site, and all required safety equipment.

Standard

S:

Push material into a stockpile approximately 5 feet in height, excavating approximately 4 - 6 inches per pass, maintain a smooth surface, and overlap each pass using 1/3 of the blade, without

- Hand signals
- Safety goggles & Gloves
- 3 Points of contact
- Ground attachments
- 360 Walk around
- Double hearing protection, Hard hats, Seat belts
- No loose clothing / jewelry
- Look in direction of travel
- Do not coast
- Caution on hills, banks, or slopes

Environmental Considerations

- Avoid unnecessary stripping and damage to vegetation and waterways.
- •Control dust conditions and limited water erosion by dressing area at the end of each day.
- •Avoid unnecessary equipment usage and follow established procedures for cleanup of fluid leaks.
- Restore site and surrounding areas


 Scoop as possible to the criais room

 The country of the criais room


 Moderate in




Start on Level Surface




Moving forward, Slowly lower blade to a 4 - 6 inch cut




{ 75 feet is only a School Standard }



Maintain a 4 - 6 inch cut for 75 feet




On Second Pass




End in same spot

Start with 1/3 blade overlap






On Third Pass.... etc.



End in same spot again Again, start with 1/3 blade overlap



ouestions

Spread a Stockpile with a Crawler Tractor

Action:

Spread a stockpile with a crawler tractor.

Conditio

ns:

Given a D7G Crawler tractor, an FM 5-434, a TM 5-2410-237-10, a LO 5-2410-237-12, at a designated training site, and all required safety equipment.

Standard

S:

Push material approximately 4 - 6 inches per pass, maintain a smooth surface, and overlap each pass using 1/3 of the blade. Perform all maneuvers in accordance with FM 5-434, TM 5-2410-237-10 and LO

- Hand signals
- Safety goggles & Gloves
- 3 Points of contact
- Ground attachments
- 360 Walk around
- Double hearing protection, Hard hats, Seat belts
- No loose clothing / jewelry
- Look in direction of travel
- Do not coast
- Caution on hills, banks, or slopes

Environmental Considerations

- Avoid unnecessary stripping and damage to vegetation and waterways.
- •Control dust conditions and limited water erosion by dressing area at the end of each day.
- •Avoid unnecessary equipment usage and follow established procedures for cleanup of fluid leaks.
- Restore site and surrounding areas


 Is close as possible to the criaissroom


 Ittion.

 Moderate in


Start on either Right or Left Side of Stock Pile


Cut into pile using 1/3 of blade







Spreading dirt evenly





tinue using 1/3 of blade cutting into the stock until the complete stockpile is leveled.





and job is complete ...





##